



**3 – POLE MAGNETIC CONTACTORS
(MADE IN S. KOREA)**

<u>SIZE</u>	<u>MODEL</u>	<u>CONTACTS ARRANGEMENT</u>	<u>CAPACITY KW / HP AC3 IEC 60947</u>	<u>OPERATIONAL CURRENT 380/ 440V AMPERES.</u>	<u>RATED THERMAL CURRENT</u>
0	MC-9a	3P+1A	4 / 5.5	9	20
0.5	MC-12a	"	5.5 / 7.5	12	20
1	MC-18a	"	7.5 / 10	18	25
0	MC-9b	3P+1A1B	4 / 5.5	9	20
0.5	MC-12b	"	5.5 / 7.5	12	20
1	MC-18b	"	7.5 / 10	18	25
1.5	MC-22b	"	11 / 15	22	32
2	MC-32a	3P+2A2B	15 / 20	32	50
2A	MC-40a	"	18.5 / 25	40	60
2.5	MC-50a	"	22 / 30	50	80
3	MC-65a	"	30 / 40	65	100
4	MC-75a	"	37 / 50	75	110
4.5	MC-85a	"	45 / 60	85	135
5	MC-100a	"	55 / 75	100	150
6	MC-130a	"	60 / 80	130	150
7	MC-150a	"	75 / 100	150	200
8	MC-185a	"	90 / 125	185	230
10	MC-225a	"	132 / 180	225	260
10A	MC-265a	"	147 / 197	265	300
11	MC-330a	"	160 / 215	330	350
12	MC-400a	"	220 / 300	400	420
13	MC-500a	"	265 / 355	500	580
14	MC-630a	"	330 / 445	630	660
16	MC-800a	"	440 / 590	800	800

AUXILIARY CONTACTORS

MR – 8 4NO + 4NC