



(KEMA  Approved)

**AIR CIRCUIT BREAKERS,
3 - POLE, 415 / 690V AC, FIXED TYPE (MADE IN S. KOREA)**

Manual Stored Energy & Fixed Mounting Type,
With 5NO + 5NC Auxiliary Contacts
& Multi - Function Overcurrent Tripping Device Providing:
Adjustable Long Time Delay (Overload Protection),
Adjustable Short Time Delay (Discrimination Protection),
Adjustable Instantaneous (Short Circuit Protection) & Pre-trip Alarm.



<u>MODEL</u>	<u>RATINGS (AMPS)</u>	<u>SETTING RANGE (AMPS)</u>	<u>AC BREAKING CAP @ 415V/500V AC IEC 947-2 (Icu = Ics)</u>
AN-10D-AG6	1000 Amps	400 to 1000 A	65 KA
AN-13D-AG6	1250 Amps	500 to 1250 A	65 KA
AN-16D-AG6	1600 Amps	640 to 1600 A	65 KA
AS-20E-AG6	2000 Amps	800 to 2000 A	85 KA
AS-25E -AG6	2500 Amps	1000 to 2500 A	85 KA
AS-32E-AG6	3200 Amps	1280 to 3200 A	85 KA
AS-40E-AG6	4000 Amps	1600 to 4000 A	85 KA

OPTIONAL ACCESSORIES & TRIPPING DEVICES:

- ◆ UNDER VOLTAGE TRIP 415/220 VAC "UVT"
- ◆ SHUNT TRIP 220 VAC "SHT"
- ◆ MOTOR MECHANISM FOR SPRING CHARGING "MD"
- ◆ CLOSING COIL "CC"
- ◆ KEY LOCK "KL"
- ◆ DRAWOUT VERSION WITH SAFETY SHUTTERS