



**MASTERPACT AIR CIRCUIT BREAKERS  
TP 660 VAC, ADJUSTABLE THERMAL TRIP**

BREAKING CAPACITY  
IEC 947-2  
Icu=Ics=Icw  
AT 415 VAC

<u>MODEL</u>	<u>RATING</u>	<u>THERMAL TRIP</u>	<u>AT 415 VAC</u>
NW08H1	800 AMPS	320 - 800 A	65 KA
NW10H1	1000 AMPS	400 - 1000 A	65 KA
NW12H1	1250 AMPS	500 - 1250 A	65 KA
NW16H1	1600 AMPS	640 - 1600 A	65 KA
NW20H1	2000 AMPS	800 - 2000 A	65 KA
NW25H1	2500 AMPS	1000 - 2500 A	65 KA
NW32H1	3200 AMPS	1280 - 3200 A	65 KA
NW40H1	4000 AMPS	1600 - 4000 A	65 KA
NW50H1	5000 AMPS	2500 - 5000 A	100 KA
NW63H1	6000 AMPS	3200 - 6300 A	100 KA

**HIGH BREAKING CAPACITY AIR CIRCUIT BREAKERS  
TP 660 VAC, ADJUSTABLE THERMAL TRIP**

NW08H2	800 AMPS	400 - 800A	100 KA
NW10H2	1000 AMPS	400 - 1000 A	100 KA
NW12H2	1250 AMPS	500 - 1250 A	100 KA
NW16H2	1600 AMPS	640 - 1600 A	100 KA
NW20H2	2000 AMPS	800 - 2000 A	100 KA
NW25H2	2500 AMPS	1000 - 2500 A	100 KA
NW32H2	3200 AMPS	1280 - 3200 A	100 KA
NW40H2	4000 AMPS	1600 - 4000 A	100 KA
NW50H2	5000 AMPS	2500 - 5000 A	150 KA
NW63H2	6000 AMPS	3200 - 6300 A	150 KA