



**3-POLE FIXED THERMAL TRIP
MOULDED CASE CIRCUIT BREAKERS**

<u>R A T I N G</u>	<u>M O D E L</u>	<u>BREAKING CAPACITY IEC 947-2 AT 415 VAC</u>	
		<u>Icu</u>	<u>Ics</u>
15, 20, 30, 40, 50 & 60 AMPS	EZC100B	7.5 KA	50 %
15, 20, 30, 40, 50, 60, 80, & 100 AMPS	EZC100F	10 KA	50 %
15, 20, 30, 40, 50, 60, 80, & 100 AMPS	EZC100N	15 KA	50 %
15, 20, 30, 40, 50, 60, 80, & 100 AMPS	EZC100H	30 KA	50 %
125, 150, 200, 225 & 250 AMPS	EZC250F	18 KA	50%
125 & 150 AMPS	EZC250N	25 KA	50%
200, 225 & 250 AMPS	EZC250N	25 KA	50%
125 & 150 AMPS	EZC250H	36 KA	50%
200, 225 & 250 AMPS	EZC250H	36 KA	50%
300 & 400 AMPS	EZC400N	36 KA	50%
300 & 400 AMPS	EZC400H	50 KA	50%

**4 – POLE ADJUSTABLE THERMAL TRIP - STANDARD MODELS
MOULDED CASE CIRCUIT BREAKERS**

<u>R A T I N G</u>	<u>THERMAL TRIP</u>	<u>M O D E L</u>	<u>BREAKING CAPACITY IEC 947-2 AT 415 VAC</u>	
			<u>Icu</u>	<u>Ics</u>
25 AMPS	20 - 25 A	NSX100F	36 KA	100 %
40 AMPS	32 - 40 A	NSX100F	36 KA	100 %
63 AMPS	50 - 63 A	NSX100F	36 KA	100 %
80 AMPS	64 - 80 A	NSX100F	36 KA	100 %
100 AMPS	80 - 100 A	NSX100F	36 KA	100 %
125 AMPS	100 - 125 A	NSX160F	36 KA	100 %
160 AMPS	120 - 160 A	NSX160F	36 KA	100 %
200 AMPS	160 - 200 A	NSX250F	36 KA	100 %
250 AMPS	200 - 250 A	NSX250F	36 KA	100 %
400 AMPS	160 - 400 A	NSX400N	50 KA	100 %
630 AMPS	250 - 630 A	NSX630N	50 KA	100 %
800 AMPS	320 - 800 A	NS 800 N	50 KA	100 %
1000 AMPS	400 - 1000A	NS1000N	50 KA	100 %
1250 AMPS	500 - 1250A	NS1250N	50 KA	100 %
1600 AMPS	640 - 1600A	NS1600N	50 KA	100 %