

**3-POLE ADJUSTABLE THERMAL TRIP  
MOULDED CASE CIRCUIT BREAKERS**



**BREAKING CAPACITY  
IEC 947-2 AT 415 VAC**

<u>RATING</u>	<u>MODEL</u>	<u>Icu</u>	<u>Ics</u>
---------------	--------------	------------	------------

**3 - POLE ADJUSTABLE THERMAL TRIP - STANDARD MODELS**

25	AMPS	20 - 25 A	CVS100B	25 KA	100 %
32	AMPS	25 - 32 A	CVS100B	25 KA	100 %
40	AMPS	32 - 40 A	CVS100B	25 KA	100 %
50	AMPS	40 - 50 A	CVS100B	25 KA	100 %
63	AMPS	50 - 63 A	CVS100B	25 KA	100 %
80	AMPS	64 - 80 A	CVS100B	25 KA	100 %
100	AMPS	80 - 100 A	CVS100B	25 KA	100 %
125	AMPS	100 - 125 A	CVS160B	25 KA	100 %
160	AMPS	120 - 160 A	CVS160B	25 KA	100 %
25	AMPS	20 - 25 A	CVS100F	36 KA	100 %
32	AMPS	25 - 32 A	CVS100F	36 KA	100 %
40	AMPS	32 - 40 A	CVS100F	36 KA	100 %
50	AMPS	40 - 50 A	CVS100F	36 KA	100 %
63	AMPS	50 - 63 A	CVS100F	36 KA	100 %
80	AMPS	64 - 80 A	CVS100F	36 KA	100 %
100	AMPS	80 - 100 A	CVS100F	36 KA	100 %
125	AMPS	100 - 125 A	CVS160F	36 KA	100 %
160	AMPS	120 - 160 A	CVS160F	36 KA	100 %
200	AMPS	160 - 200 A	CVS250F	36 KA	100 %
250	AMPS	200 - 250 A	CVS250F	36 KA	100 %
400	AMPS	160 - 400 A	CVS400F	36 KA	100 %
630	AMPS	250 - 630 A	CVS630F	36 KA	100 %
400	AMPS	160 - 400 A	CVS400N	50 KA	100 %
630	AMPS	250 - 630 A	CVS630N	50 KA	100 %