



**3-POLE ADJUSTABLE THERMAL TRIP
MOULDED CASE CIRCUIT BREAKERS**

BREAKING CAPACITY
IEC 947-2 AT 415 VAC

<u>RATING</u>	<u>MODEL</u>	<u>Icu</u>	<u>Ics</u>
---------------	--------------	------------	------------

3-POLE ADJUSTABLE THERMAL TRIP - STANDARD MODELS

16	AMPS	12.5 - 16 A	NSX100F	36 KA	100 %
25	AMPS	20 - 25 A	NSX100F	36 KA	100 %
32	AMPS	25 - 32 A	NSX100F	36 KA	100 %
40	AMPS	32 - 40 A	NSX100F	36 KA	100 %
50	AMPS	40 - 50 A	NSX100F	36 KA	100 %
63	AMPS	50 - 63 A	NSX100F	36 KA	100 %
80	AMPS	64 - 80 A	NSX100F	36 KA	100 %
100	AMPS	80 - 100 A	NSX100F	36 KA	100 %
125	AMPS	100 - 125 A	NSX160F	36 KA	100 %
160	AMPS	120 - 160 A	NSX160F	36 KA	100 %
200	AMPS	160 - 200 A	NSX250F	36 KA	100 %
250	AMPS	200 - 250 A	NSX250F	36 KA	100 %
400	AMPS	160 - 400 A	NSX400N	50 KA	100 %
630	AMPS	250 - 630 A	NSX630N	50 KA	100 %
800	AMPS	320 - 800 A	NS 800 N	50 KA	75 %
1000	AMPS	400 - 1000A	NS1000N	50 KA	75 %
1250	AMPS	500 - 1250A	NS1250N	50 KA	75 %
1600	AMPS	640 - 1600A	NS1600N	50 KA	75 %

3-POLE ADJUSTABLE THERMAL TRIP - HIGH BREAKING CAPACITY

16	AMPS	12.5 - 16 A	NSX100H	70 KA	100 %
25	AMPS	20 - 25 A	NSX100H	70 KA	100 %
40	AMPS	32 - 40 A	NSX100H	70 KA	100 %
63	AMPS	50 - 63 A	NSX100H	70 KA	100 %
80	AMPS	64 - 80 A	NSX100H	70 KA	100 %
100	AMPS	80 - 100 A	NSX100H	70 KA	100 %
160	AMPS	120 - 160 A	NSX160H	70 KA	100 %
200	AMPS	160 - 200 A	NSX250H	70 KA	100 %
250	AMPS	200 - 250 A	NSX250H	70 KA	100 %
400	AMPS	160 - 400 A	NSX400H	70 KA	100 %
630	AMPS	250 - 630 A	NSX630H	70 KA	100 %
800	AMPS	320 - 800 A	NS 800 H	70 KA	100 %
1000	AMPS	400 - 1000 A	NS1000H	70 KA	100 %
1250	AMPS	500 - 1250 A	NS1250H	70 KA	100 %
1600	AMPS	640 - 1600 A	NS1600H	70 KA	100 %

