

**MOULDED CASE CIRCUIT BREAKERS - 3 POLE
WITH ADJUSTABLE THERMAL / ELECTRONIC TRIP
(MADE IN S. KOREA)**



<u>RATINGS</u>	<u>MODEL</u>	<u>THERMAL TRIP</u>	AC BREAKING CAPACITY
			IEC 947-2 415/440VAC (KA) <u>Icu / Ics</u>
16 AMPS.	TD100N - FMU	12 – 16A	50 / 50
25 AMPS.	TD100N - FMU	20 – 25A	50 / 50
32 AMPS.	TD100N - FMU	25 – 32A	50 / 50
40 AMPS.	TD100N - FMU	32 – 40A	50 / 50
50 AMPS.	TD100N - FMU	40 – 50A	50 / 50
63 AMPS.	TD100N - FMU	50 – 63A	50 / 50
80 AMPS.	TD100N - FMU	64 – 80A	50 / 50
100 AMPS.	TD100N - FMU	80 – 100A	50 / 50
125 AMPS.	TS160N - ATU	100 – 125A	50 / 50
160 AMPS.	TS160N - ATU	125 – 160A	50 / 50
200 AMPS.	TS250N - ATU	160 – 200A	50 / 50
250 AMPS.	TS250N - ATU	200 – 250A	50 / 50
400 AMPS.	TS400N - ETS	160 – 400A	50 / 50
630 AMPS.	TS630N - ETS	250 – 630A	65 / 65
800 AMPS.	TS800N - ETS	320 – 800A	65 / 65
1000 AMPS.	TS1000N – AG5	400 – 1000A	65 / 65
1200 AMPS.	TS1250N – AG5	500 – 1250A	65 / 65
1600 AMPS.	TS1600N - AG5	640 – 1600A	65 / 65