

**MOULDED CASE CIRCUIT BREAKERS,
3-POLE, 500/600 V , WITH THERMAL & MAGNETIC TRIPS
(MADE IN JAPAN)**



<u>RATINGS (AMPS.)</u>	<u>MODEL</u>	<u>AC BREAKING CAPACITY IEC 947-2 (KA)</u>
		415V <u>Icu/Ics</u>
3, 5, 10, 15, 20 & 30 AMPS	BW32-AAG	1.5 / 1
3, 5, 10, 15, 20 & 30 AMPS	BW32-SAG	2.5 / 2
40 & 50 AMPS	BW50-EAG	2.5 / 2
5, 10, 15, 20, 30, 40 & 50 AMPS	BW50-SAG	7.5 / 4
10, 15, 20, 30, 40 & 50 AMPS	BW50-RAG	10 / 5
60 AMPS.	BW63-EAG	2.5 / 2
60 AMPS.	BW63-SAG	7.5 / 4
60, 75 & 100 AMPS.	BW100-EAG	10 / 5
150 AMPS.	BW160-EAG	18 / 9
200 & 225 AMPS.	BW250-EAG	18 / 9
250 AMPS.	BW250-EAG	18 / 9
300 & 400 AMPS.	BW400-EAG	30 / 15
500 & 600 AMPS.	BW630-EAG	36 / 18
800 AMPS.	BW800-RAG	50 / 25
1000 AMPS. ADJ.SET.: 500-1000A	SA-1003E	65 / 49
1200 AMPS. ADJ.SET.: 600-1200A	SA-1203E	65 / 49