

**MOULDED CASE CIRCUIT BREAKERS
3 POLE WITH THERMAL & MAGNETIC TRIPS
(MADE IN S. KOREA)**



| <u>STANDARD BREAKING CAPACITY RATINGS (AMPERES)</u> | <u>M O D E L</u> | <u>AC BREAKING CAPACITY IEC 947-2 AT 415 VAC</u> | |
|---|------------------|--|-----------------------|
| | | <u>I_{cu}</u> | <u>I_{cs}</u> |
| 3, 5 & 10 AMPS. | ABS - 33c | 10 KA | 100% |
| 15, 20 & 30 AMPS. | ABS - 33c | 14 KA | 100% |
| 40 & 50 AMPS. | ABN - 53c | 14 KA | 100% |
| 60, 75 & 100 AMPS. | ABN - 103c | 18 KA | 100% |
| 125, 150, 200 & 225 AMPS. | ABN - 203c | 26 KA | 100% |
| 250 AMPS | ABN - 203c | 26 KA | 100% |
| 300 & 400 AMPS. | ABN - 403c | 37 KA | 100% |
| 500 & 630 AMPS. | ABN - 803c | 37 KA | 100% |
| 800 AMPS. | ABN - 803c | 37 KA | 100% |

HIGH BREAKING CAPACITY

| | | | |
|---------------------------|-------------|-------|------|
| 15, 20, 30, 40 & 50 AMPS. | ABH - 53c | 50 KA | 100% |
| 60, 75, 100 AMPS. | ABH - 103c | 50 KA | 100% |
| 125 AMPS | ABH - 103c | 50 KA | 100% |
| 150, 200 & 225 AMPS. | ABH - 203c | 50 KA | 100% |
| 250 AMPS. | ABH - 203c | 50 KA | 100% |
| 300 & 400 AMPS. | ABH - 403c | 65 KA | 100% |
| 500 & 630 AMPS. | ABS - 803c | 65 KA | 100% |
| 800 AMPS. | ABS - 803c | 65 KA | 100% |
| 1000 AMPS. | ABS - 1003b | 65 KA | 100% |
| 1200 AMPS. | ABS - 1203b | 65 KA | 100% |