



**POWER FACTOR CAPACITORS
3 – PHASE, 50 HZ (MADE IN JAPAN)**

<u>DESCRIPTION</u>	<u>VOLTAGE</u>	<u>MODEL</u>
50 KVAR	415 VAC	RF

**POWER FACTOR CAPACITORS
3 – PHASE, 50 HZ (MADE IN THAILAND)**

12.5 KVAR	415 VAC	RFT
25 KVAR	415 VAC	RFT
25 KVAR	415 VAC	RG-2
25 KVAR	460 VAC	RG-2
50 KVAR	415 VAC	RG-2
50 KVAR	460 VAC	RG-2
50 KVAR	600 VAC	RG-2

FEATURES

- * DESIGNED, MANUFACTURED TESTED TO MEET LATEST STANDARD IEC PUBLICATION No. 70, 70A, 593 & JIS C 4901
- * CONTAINER MADE OF STAINLESS STEEL, OR ROLLED MILD STEEL COATED WITH NON-CORROSION POLY URETHANE RESIN ENAMEL OR PATHALIC ACID ENAMEL IN MUNSELL COLOUR TO EXTEND MAINTENANCE FREE LIFE.
- * PROVIDE WITH BUILT-IN-DISCHARGE RESISTORS TO REDUCE RESIDUAL VOLTAGE FROM CREST TO 50 VOLTS OR LESS WITHIN A MAX. TIME OF 1 MIN. AFTER ALLIED VOLTAGE WITHDRAWN.
- * PROVIDE WITH INTERNAL OVER PRESSURE DISCONNECTOR TO PROTECT CAPACITOR AND INTRUPPTING INTERNAL CONNECTIONS IN EVENT OF AN ELEMENT FAILURE.
- * AMBIENT TEMPERATURE : -10 'C TO +45 'C
- INSULATION LEVEL : 3KVrms / 15 KV CREST
- FUNCTION : INHERENT SELF HEALING
- LOSSES : EXTREMELY LOW