



AF94-410

■ **Super Timers**

● **MS4S/Multimode and compact body**

The MS4S is a timer with four operation modes. The on-delay, flicker, one-shot or signal off-delay operation modes can be selected.

SUPER TIMERS (MADE IN JAPAN)

<u>MODEL</u>	<u>DESCRIPTION</u>
MS4S-A-AP	CONTACT TIMED 2 PDT, 5A, ON-DELAY, 8-PIN INPUT VOLTAGE 100 TO 240V AC, 50 Hz. TIME RANGES : 0.6 SEC. TO 60 HOUR
MS4S-A-DB	INPUT VOLTAGE 12V DC
MS4S-M-AP	CONTACT TIMED : 2 PDT 5A, ON DELAY, 11-PIN OPERATION MODE SELECTABLE FLICKER OPERATION (REPEAT CYCLE) FL ONE-SHOT MOMENTARY (ACTUATION) OS SIGNAL OFF DELAY (SF) INPUT VOLTAGE : 100 TO 240V AC, 50 Hz. TIME RANGES : 0.6 SEC. TO 60 HOUR
MS4S-M-DB	INPUT VOLTAGE – 12V DC
MS4S-Y-AP	STAR DELTA TIMER, 8-PIN TIME : 6 SEC. TO 120 SEC. INPUT VOLTAGE: 100 TO 240 VAC, 50 HZ
MS4S-F-AP	CONTACT TIMED 2 PDT, 5A, OFF-DELAY, 8-PIN INPUT VOLTAGE 100 TO 240V AC, 50 Hz. TIME RANGES : 0.6 SEC. TO 12 MINUTES