


**THERMAL OVERLOAD RELAYS
(MADE IN S. KOREA)**



- WITH a) SINGLE PHASE PREVENTING DEVICE FOR PHASE FAILURE PROTECTION.
 b) 3-ELEMENTS, SEPERATE MOUNTED.
 c) MANUAL & AUTOMATIC RESET FACILITY.

<u>MODEL</u>	<u>AMPERE RANGE.</u>
MT-12/3K	0.63-1, 1-1.6, 1.6-2.5, 2.5-4, 4-6, 5-8 6-9, 9-13 & 12-18 AMPS.
MT-32/3K	16-22, 22-32, 28-40 AMPS.
MT-63/3K	34-50, 45-65 AMPS.
MT-95/3K	63-85, 80-100 AMPS.
MT-150/3K	95-130, 110-150 AMPS.
MT-225/3K	160-240 AMPS.
MT-400/3K	260-400 AMPS
MT-800/3K	400-600, 520-800 AMPS.

**3-ELEMENTS, MANUAL & AUTOMATIC RESET FACILITY,
PIN TYPE RELAYS.**

MT-12/3H	FOR 9a, 12a & 18a CONTACTORS	0.63-1, 1-1.6, 1.6-2.5, 2.5-4, 4-6, 5-8, 6-9 9-13, 12-18, AMPS.
MT-32/3H	FOR 9b, 12b & 18b CONTACTORS	1-1.6, 1.6-2.5, 2.5-4, 4-6, 6-9 9-13, 12-18, AMPS.

ELECTRONIC MOTOR PROTECTION RELAY-EMPR (MADE IN S. KOREA)

GMP60-T	0.5 – 6 AMPS. 5 – 60 AMPS.
SUPPLY VOLTAGE	: AC 160 ~ 230V 50/60Hz : AC 340 ~ 480V 50/60Hz
DELAY TIME SETING	: 1 to 30 Sec.
OPERATING SETTING TIME	: 1 to 15 Sec.
CONTACT RATING	: 5A, 250V AC
OVER CURRENT PROTECTION FUNCTION	: 105 ~ 115% OF THE SET CURRENT.